


PC software for Höntzsch hand-held units for configuration, readout and processing of measured data



Datalogger

HLOG II allows readout of the data saved to the hand-held unit.

Display

The transferred data can be displayed numerically in a spreadsheet which can be formatted and also as an interactive line chart.

Saving data

All data can be permanently archived under an individual identifier.

Configuration

With the HLOG II all settings can be readout, changed and saved. Individual linearising of characteristics for reducing measurement uncertainty is easily done on the PC.

Data exchange

XLS or CSV files can be generated to export numerical data. Charts are exported as JPG file.

Print-out

Spreadsheets, charts, settings and pairs of values can be printed. Fit the data to size if necessary before printing.

Statistics functions

- number of rows (groups)
- number of data sets
- total time of all measurements
- min. value
- max. value
- average





Compatibility

Data exchange is possible with the following Höntzsch units:

- flowtherm NT
- HTA, HTA-Ex
- HFA, HFA-Ex
- HVA

Software version 1.9 upwards is necessary for full use of the HLOG II functions in Höntzsch HxA units. A software update can be carried out by Höntzsch.

PC / hand-held unit connection

The flowtherm NT is equipped with a USB interface with which it can be connected directly to a PC. HFA, HFA-Ex, HTA, HTA-Ex and HVA have an RS232 interface. Here a special adapter cable is necessary for connecting to a PC. A Höntzsch converter is available for converting an RS232 to a USB interface.

System requirements

- Windows 98 (SP2), later version recommended
- at least Pentium III
- 256 MB RAM, 512 MB recommended
- approx. 100 MB free memory on the hard drive

Menu navigation

German, English

Prompts

User assistance via the help function. Retrieval of information such as Data Sheets and Operating Instructions.

Order information / Accessories	
	Art. No.
Software set HLOG II (flowtherm NT) Software for displaying data on a PC incl. 1.8 m USB cable and carrying case	HB00-a522
Software set HLOG II (HTA-Ex, HFA, HFA-Ex, HVA) Software for displaying data on a PC incl. 1.5 m RS-232 connection cable and carrying case, connector 680-6 / D-SUB 9-pin	HB00-a520
Software set HLOG II (HTA) Software for displaying data on a PC incl. 1.5 m RS-232 connection cable case, connector 680-8 / D-SUB 9-pin	HB00-a521
Software update HLOG to HLOG II	HB 00 -a 525
Interface converter USB/RS232	HB00-a100



Höntzsch GmbH

Gottlieb-Daimler-Straße 37 D-71334 Waiblingen (Hegnach) Tel: +49 7151 / 17 16-0 Fax: +49 7151 / 5 84 02 E-Mail info@hoentzsch.site Internet www.hoentzsch.site